

# SULIS Q

Plafone.

Struttura in alluminio pressofuso.  
Finitura in bianco,  
grigio antracite o marrone.  
Diffusore in vetro temperato satinato.

Ceiling light.





Die-cast aluminium structure.  
White, grey graphite or brown finish.  
Frost tempered glass diffuser.



LIGHT SOURCE		FINISHED	CODE	BULBS	
GU10 max 1 x 35W 220-240Vac  Lampadine non incluse Bulbs not included.		Bianco White	<b>GES1070</b>	1 x GU10	
		Grigio antracite Gray graphite	<b>GES1071</b>	1 x GU10	
		Marrone Brown	<b>GES1072</b>	1 x GU10	

## LAMPADINE UTILIZZABILI AVAILABLE BULBS

Vedi pagina / see page  
479

GU10	BEAM	CODE	POWER	CCT	FLUX	CRI
		GLA241C	5W	3000K	420lm	>80
		GLA241N	5W	4000K	430lm	>80
		GLA243C	7W	3000K	590lm	>80
		GLA243N	7W	4000K	610lm	>80
		GLA242C	5W	3000K	410lm	>80
		GLA242N	5W	4000K	420lm	>80
		GLA244C	7W	3000K	550lm	>80
		GLA244N	7W	4000K	560lm	>80