














Illustrative picture

**SPECIFICS**

<i>Description</i>	Product type	5 sockets schuko/Biv 10/16A 2P+E 250V 1,5m cable H05VV-F 3G1 +LED warning light + plug 16A 2P+E 250V Italian Standard P30 P17/11 S17
	Article code	<b>RS94006</b>
	Commercial Series	MULTIPLE SOCKETS - SERIES EMILIA SCHUKO BIVALENT

<i>General Data</i>	Poles	N° 2P+E	Type of material	Blend,Nylon						
	Current	A 16	Dimensional stability	°C -25 /+70						
	Voltage	V~ 250	Resistance glow wire test	°C +650 / +850						
	Degree of protection	IP 20	Working temperature	°C , -15 + 35						
	Impact Resistance	IK 8	Weight	kg 0.30						
	Insulation Resistance	MΩ >10								
	Dimensions LxDxH	cm 27X8X4								
	Behaviour with chemical and atmospheric agents									
	Acids		Bases		Solvents			Mineral Oil	UV rays	
Saline Solution	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant 	Limited Resistant 	Resistant 	Resistant 	Resistant 	Limited Resistant 	Limited Resistant 	Resistant 	Resistant 	Resistant 	Resistant 

<i>Standards</i>	CEI 23-50	2014/35/UE
------------------	-----------	------------

<i>Features package</i>	<i>Descriptions</i>	<i>N/pieces</i>	<i>Weight/kg</i>
	Article	1	0.30
	Package innerbox	25	7.6
	Packaging		



Rev	Date	Technical Manager
01	7/IV/20	<i>Romano Rosi</i>